

SHEKEL MERAV 2000 S/P **Industrial Application Indicators**



SANS 1649 compliant -**Legal for Trade**



Standard specifications:

- ▶ 6 digits 1" LCD Display
- > All functions are programmable using 4 keys
- > Flexible decimal point
- > Division: 1, 2, 5, 10, 20, 100, 200, 500
- > Accuracy: 3000d suits OIML-H44 standards
- > Resolution: 10000d, 120000 internal divisions
- > Analog / Digital Filter, analog signal with 3.3µV/sec sensitivity
- > Auto Tare and manual Tare input
- \succ Connects up to 12 load cells 3500hm,
- p/supply 5V-10V to each load cell
- ▶ Power source 50/60 Hz 230 VAC
- \succ Weight memory
- > EASY PANEL MOUNT HOUSING

Model & Specifications:

MERAV 2000 S/P (for batching - 4 x set-point controller)

- \succ Up to 12 x Load cells.
- ▶ Power: 220VAC mains
- > Built-in 4 x set point controller
- > Weight memory


Optional - Stainless steel housing MERAV 2000 DENISE S/P (with 4 x set-point)

- > Specifications as above
- > Fully stainless steel IP67 housing











Optional: PANEL MOUNT



Specifications:

- PVC Box
- Pilot lights
- Start & Stop button
- Power Supply/Mini-Rel
- Surpressor
- 4 X Relays
- Cabling & connectors



Process control applications

