



SHEKEL MERAV 2000 O/P Indicator

Industrial Application



**SANS 1649 compliant -
Legal for Trade**



Standard specifications:

- 6 digits 1" LCD Display
- All functions are programmable using 4 keys
- Flexible decimal point
- Division: 1, 2, 5, 10, 20, 100, 200, 500
- Accuracy: 3000d suits OIML-H44 standards
- Resolution: 10000d, 120000 internal divisions
- Analog / Digital Filter, analog signal with 3.3µV/sec sensitivity
- Auto Tare and manual Tare input
- Connects up to 12 load cells 350ohm, p/supply 5V-10V to each load cell
- Power source 50/60 Hz 230 VAC
- RS232 Communication to PC or printer
- Weight memory
- **EASY PANEL MOUNT HOUSING**

Model & Specifications:

MERAV 2000 O/P **(for PLC - Programmable Logic Controller)**

- Up to 12 x Load cells,
- Power: 220VAC mains only
- 4-20mA output, 0-10V, BCD,
- RS232 output
- Weight memory

Optional - Stainless steel housing

MERAV 2000 DENISE O/P

- Specifications as above
- Fully stainless steel IP67 housing



Process control applications



Optional: PANEL MOUNT



Specifications:

- PVC Box
- Pilot lights
- Start & Stop button
- Power Supply/Mini-Rel
- Suppressor
- 4 X Relays
- Cabling & connectors

