

PRECISIO 7 - GY7170-150 Ex - AUTO (ONLY ON EQUEST)



Applicable using 48kg DV BOTTLES supply - WITH AUTO SWITCH-OFF CIRCUIT

SABS Explosive-proof Ex ib IIC T4 approved & SABS for Trade-use approved
Suitable for filling material: Liquefied petroleum gas (LPG) and other liquefied gas with less than Class Ex ib IIC T4 IA
Certificate No.: SABS S/13-379 X Certification: ZONE 1 & 2

Specifications:

- Ex approved - for transferring from 3kg up to 48kg via electronic LPG filling

PRECISIO 7 - GY7170 - AUTO

Stock Code:	PRECISIO 7
Description:	PRECISIO 7 - GY7170A - AUTO
Specifications:	Ex approved - Applicable using 48kg DV bottles (FOR TRADE-USE)

Excl. VAT

SPARE BATTERY

Stock Code:	GY7170-150 BATT
-------------	-----------------

Excl. VAT



Applications:

- § Power: 2000mAh Lithium-ion Re-chargeable battery.
- § Battery charger included with an additional battery & battery drum.
- § **Battery operation:** minimum 45hrs
- § Pressure: 0 - 1.6MPa (16Bar)

Capacity x Accuracy: 150kg x 50g

Features:

- § Precision / Accuracy: Class III
- § Quantitative Filling
- § **Optional for auto cut-off of pump if using series of DV 48kg bottle supplies or continues if using BULK tank supply with by-pass loop.**
- § Ex Intrinsically-safe Explosive-proof
- § Safe and reliable, Simple and convenient
- § One key set / preset weights
- § From small 3kg bottles up to 48kg & forklift bottle filling
- § Automatic tare of the filling gun and bottle weight, filling convenient operation
- § Platform Dimensions: 40cm x 50cm x 5mm chequered top plate for long lasting
- § Dimension(L*W*H): 40 x 80 x 1,5mHeight
- § Weight: 67kg

Optional:

- § **Elevated waist height flip platform**
- § Remote stand for indicator
- § Two size bottle filling valves
- § SMITH/ELNOR LPG transfer pump



General explanation:

Integral check-weigher with refill function ensures filling tolerance compliance. An automatic go-to-zero of tare value and thus automatically to recuperate the residue gas, which eliminates overfilling. Gas filling totals on-board including residual, gas added and saleable gas. A START button with highly reliable long lasting electronic valve starts the auto process. Tare zone check ensures correct fill program per cylinder.