GM model C101A-15KG
Dynamic Checkweigher

Suitable for multi-industry applications heavy load, bags, soft-sided containers and bottles

Multi-industry application

Specifications:

■ Platform material/Frame: 201 Stainless steel/Carbon steel paint	
■ Scale division: 2g (accuracy - +/-2g)	
■ Weighing range: 0,1kg - 15kg	
■ Weighing speed: 80 pcs/min	
■ Belt speed: 8 - 80meter/min	
■ Platform size: 880 x 600mm	
■ Height: 750 +/- 50mm	
■ Display size: 10 inch	
■ Alarm light: 3-color signal light	
■ Rejection mechanism: user customized	
■ Data storage: 100 sets of parameters	
■ Communication: RS485 (Modbus RTU)/Modbus TCP/IP	
■ Air pressure: user customized (Mpa)	
■ IP grade: IP54	

■ Heavy load, for product weight up to 15kg, with accuracy under 5 grams.

■ For pouches, bags, soft-sided containers, and bottles.

■ Easy to operate with touch screen, can store 100 different products.

■ With different rejector options, can also integrate with metal detector.

Excludes rejector

10-inch user friendly touch screen and graphical design interface. Simple operation without professional training.

60.000 kg

■ A million product formula storage. Users/Admin can easy add or delete data.

■ Product formula with detection parameters setup by admin.

■ 3 levels of administration authority for well-organized management.

Since 1988